

# **EXHIBIT 6**

**Electronic Acknowledgement Receipt**

<b>EFS ID:</b>	15805994
<b>Application Number:</b>	13896829
<b>International Application Number:</b>	
<b>Confirmation Number:</b>	7048
<b>Title of Invention:</b>	Controlling and manipulating groupings in a multi-zone media system
<b>First Named Inventor/Applicant Name:</b>	Robert A Lambourne
<b>Customer Number:</b>	14458
<b>Filer:</b>	Christopher Neith George
<b>Filer Authorized By:</b>	
<b>Attorney Docket Number:</b>	20218/13-0504
<b>Receipt Date:</b>	17-MAY-2013
<b>Filing Date:</b>	
<b>Time Stamp:</b>	15:41:35
<b>Application Type:</b>	Utility under 35 USC 111(a)

**Payment information:**

Submitted with Payment	yes
Payment Type	Electronic Funds Transfer
Payment was successfully received in RAM	\$ 1600
RAM confirmation Number	2337
Deposit Account	
Authorized User	

**File Listing:**

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
		Page 1 of 44			

Case 3:20-cv-06754-WHA Document 723-8 Filed 05/14/23 Page 3 of 45

1		13-0504_Specifications_5-17-13.pdf	857481 3dcd1a66cb76c90dfc0dc45173af73e67da96ab	yes	27
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	21	
	Claims		22	26	
	Abstract		27	27	
Warnings:					
Information:					
2	Transmittal of New Application	13-0504_New_Transmittal_of_App.pdf	276037 52011321ce2d8ffdc417f54c98fd80efd0201984	no	2
Warnings:					
Information:					
3	Transmittal Letter	13-0504_New_Fee_Transmittal.pdf	255716 b82ba5647a9fce5dda28da4ed2f87f1c3a7fa8f0	no	2
Warnings:					
Information:					
4	Application Data Sheet	13-0504_ADS_5-17-13_2.pdf	71140 9fd3c872e4a86bfb8bbd75a789cd699f8540f5e	no	6
Warnings:					
Information:					
This is not an USPTO supplied ADS fillable form					
5	Information Disclosure Statement (IDS) Form (SB08)	13-0504_IDS_5-17-13_2.pdf	46065 a4e7d2c92415927e29cd17dd483449a31dfb2ff9	no	5
Warnings:					
Information:					
This is not an USPTO supplied IDS fillable form					
6	Power of Attorney	General_POA_Sonos_4-29-2011.pdf	82905 f78478cfebf4282a7298f696ca98df6473e8427f	no	2
Warnings:					
Information:					
7	Oath or Declaration filed	SignedDeclaration.pdf	775369 4bf5e91bf7ce10fa8adee799f232373a99bae06	no	2

Warnings:					
Information:					
8	Assignee showing of ownership per 37 CFR 3.73.	13-0502_37CFR373b.pdf	36349	no	2
			1a9116843ca5676ab8059adc81d380891ccac00b		
Warnings:					
Information:					
9	Foreign Reference	FPT.pdf	21825	no	2
			baf4501a2562cd5baf8887b25db8572e3a5b2c24		
Warnings:					
Information:					
10	Non Patent Literature	NPL1.pdf	145926	no	3
			503ff132f750bb75a4f77df983873a553eba7f4b		
Warnings:					
Information:					
11	Non Patent Literature	NPL2.pdf	322045	no	9
			b534b6f61d4294e20a3eedc94c89524c2f71b995		
Warnings:					
Information:					
12	Non Patent Literature	NPL3.pdf	203847	no	4
			a359bfd03a4ac0ef183ed089388cc5a54d1a508		
Warnings:					
Information:					
13	Non Patent Literature	NPL4.pdf	317865	no	9
			1bbbe24f7e4fe0151fc15f0f4fbfc7b950e87cd9		
Warnings:					
Information:					
14	Non Patent Literature	NPL5.pdf	3033392	no	54
			3e4c92fbe77a5e6cac0db60710099f92e2bb52fc		
Warnings:					
Information:					
15	Non Patent Literature	NPL6.pdf	1397150	no	24
			8934714ded14f7148d588fdb18aefe813d076f6		
Warnings:					
Information:					
16	Non Patent Literature	NPL7.pdf	9227271	no	70
			8d4e6c87f5e5f569a62b262a165b0dcbab9e9c0a		

Page 3 of 44



<b>Warnings:</b>					
<b>Information:</b>					
17	Non Patent Literature	NPL8.pdf	2153748 a93f558ebc529d680777e8735c18aadddb2a7848	no	32
<b>Warnings:</b>					
<b>Information:</b>					
18	Non Patent Literature	NPL09.pdf	3191339 505de48d6df12aebcb83aaf0616eb419721c1d8f	no	296
<b>Warnings:</b>					
<b>Information:</b>					
19	Drawings-only black and white line drawings	13-0504_Figures_filed.pdf	306327 290479f1e745208fb21a3b8795aa09ff4bf862f7	no	11
<b>Warnings:</b>					
<b>Information:</b>					
20	Fee Worksheet (SB06)	fee-info.pdf	32595 2bc0d3bd79d27d316abb96b664fb2d19f8218a3a	no	2
<b>Warnings:</b>					
<b>Information:</b>					
<b>Total Files Size (in bytes):</b>			22754392		
<p><b>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</b></p> <p><b><u>New Applications Under 35 U.S.C. 111</u></b>  <b>If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</b></p> <p><b><u>National Stage of an International Application under 35 U.S.C. 371</u></b>  <b>If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</b></p> <p><b><u>New International Application Filed with the USPTO as a Receiving Office</u></b>  <b>If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</b></p>					

PTO/AIA/15 (03-13)

Approved for use through 01/31/2014. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995 no persons are required to respond to a collection of information unless it displays a valid OMB control number

<b>UTILITY PATENT APPLICATION TRANSMITTAL</b>  <i>(Only for new nonprovisional applications under 37 CFR 1.53(b))</i>		Attorney Docket No. <b>20218/13-0504</b>	
		First Named Inventor <b>Robert A Lambourne</b>	
		Title <b>Controlling and manipulating groupings in a multi-zone media system</b>	
		Express Mail Label No.	

<b>APPLICATION ELEMENTS</b> <i>See MPEP chapter 600 concerning utility patent application contents.</i>	<b>Commissioner for Patents</b> <b>P.O. Box 1450</b> <b>Alexandria, VA 22313-1450</b>
1. <input checked="" type="checkbox"/> <b>Fee Transmittal Form</b> (PTO/SB/17 or equivalent) 2. <input type="checkbox"/> <b>Applicant asserts small entity status.</b> See 37 CFR 1.27 3. <input type="checkbox"/> <b>Applicant certifies micro entity status.</b> See 37 CFR 1.29. Applicant must attach form PTO/SB/15A or B or equivalent. 4. <input checked="" type="checkbox"/> <b>Specification</b> [Total Pages <u>27</u> ] Both the claims and abstract must start on a new page. (See MPEP § 608.01(a) for information on the preferred arrangement) 5. <input checked="" type="checkbox"/> <b>Drawing(s)</b> (35 U.S.C. 113) [Total Sheets <u>11</u> ] 6. <b>Inventor's Oath or Declaration</b> [Total Pages <u>2</u> ] (including substitute statements under 37 CFR 1.64 and assignments serving as an oath or declaration under 37 CFR 1.63(e)) a. <input type="checkbox"/> Newly executed (original or copy) b. <input checked="" type="checkbox"/> A copy from a prior application (37 CFR 1.63(d)) 7. <input checked="" type="checkbox"/> <b>Application Data Sheet</b> * See note below. See 37 CFR 1.76 (PTO/AIA/14 or equivalent) 8. <b>CD-ROM or CD-R</b> in duplicate, large table, or Computer Program (Appendix) <input type="checkbox"/> Landscape Table on CD 9. <b>Nucleotide and/or Amino Acid Sequence Submission</b> (if applicable, items a. – c. are required) a. <input type="checkbox"/> Computer Readable Form (CRF) b. <input type="checkbox"/> Specification Sequence Listing on: i. <input type="checkbox"/> CD-ROM or CD-R (2 copies); or ii. <input type="checkbox"/> Paper c. <input type="checkbox"/> Statements verifying identity of above copies	<b>ACCOMPANYING APPLICATION PAPERS</b> 10. <input type="checkbox"/> <b>Assignment Papers</b> (cover sheet & document(s)) Name of Assignee _____ 11. <input checked="" type="checkbox"/> <b>37 CFR 3.73(c) Statement</b> <input checked="" type="checkbox"/> <b>Power of Attorney</b> (when there is an assignee) 12. <input type="checkbox"/> <b>English Translation Document</b> (if applicable) 13. <input type="checkbox"/> <b>Information Disclosure Statement</b> (PTO/SB/08 or PTO-1449) <input type="checkbox"/> Copies of citations attached 14. <input type="checkbox"/> <b>Preliminary Amendment</b> 15. <input type="checkbox"/> <b>Return Receipt Postcard</b> (MPEP § 503) (Should be specifically itemized) 16. <input type="checkbox"/> <b>Certified Copy of Priority Document(s)</b> (if foreign priority is claimed) 17. <input type="checkbox"/> <b>Nonpublication Request</b> Under 35 U.S.C. 122(b)(2)(B)(i). Applicant must attach form PTO/SB/35 or equivalent. 18. <input type="checkbox"/> <b>Other:</b> _____ _____ _____ _____ _____

**\*Note:** (1) Benefit claims under 37 CFR 1.78 and foreign priority claims under 1.55 **must** be included in an Application Data Sheet (ADS).  
 (2) For applications filed under 35 U.S.C. 111, the application must contain an ADS specifying the applicant if the applicant is an assignee, person to whom the inventor is under an obligation to assign, or person who otherwise shows sufficient proprietary interest in the matter. See 37 CFR 1.46(b).

<b>19. CORRESPONDENCE ADDRESS</b>				
<input checked="" type="checkbox"/> The address associated with Customer Number: <u>34431</u> OR <input type="checkbox"/> Correspondence address below				
Name				
Address				
City	State	Zip Code		
Country	Telephone	Email		

Signature	/Christopher N. George/	Date	05-17-2013
Name (Print/Type)	Christopher N. George	Registration No. (Attorney/Agent)	51,728

This collection of information is required by 37 CFR 1.53(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

## Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

**In the United States Patent and Trademark Office**

**Utility Application**

**for**

**Controlling and manipulating groupings in a multi-zone media system**

Inventor: Robert A. Lambourne  
3722 Cedar Vista  
Santa Barbara, CA 93110  
Citizenship: United Kingdom



## **Controlling and manipulating groupings in a multi-zone media system**

Robert A. Lambourne

### **CROSS REFERENCE TO RELATED APPLICATION**

[0001] This application is a continuation of and claims priority to Patent Application Serial No. 11/853,790, filed September 11, 2007, entitled "CONTROLLING AND MANIPULATING GROUPINGS IN A MULTI-ZONE MEDIA SYSTEM," and U.S. Provisional Application No. 60/825,407 filed on September 12, 2006, entitled "CONTROLLING AND MANIPULATING GROUPINGS IN A MULTI-ZONE MEDIA SYSTEM," each of which is hereby incorporated by reference in its entirety for all purposes.

### **BACKGROUND OF THE INVENTION**

#### **Field of the Invention**

**[0002]** The invention is generally related to the area of consumer electronics and human-computer interaction. In particular, the invention is related to method and apparatus for controlling or manipulating a plurality of multimedia players in a multi-zone system.

**[0003]** An enduring passion for quality audio reproduction or system is continuing to drive demands from users. One of the demands includes an audio system in a house in which, for example, one could grill to classic rock on a patio while another one may cook up his/her own music selections in a kitchen. This is all at the same time while a teenager catches a ballgame in a family room, and another one blasts pop in a bedroom. And the best part of such audio system is that each family member does not need his or her own stereo system - one system gives everyone access to all the music sources.

**[0004]** Currently, one of the systems that can meet part of such demand is a conventional multi-zone audio system that usually includes a number of audio players. Each of the audio players has its own amplifier(s) and a set of speakers and typically installed in one place (e.g., a room). In order to play an audio source at one location, the audio source must be provided locally or from a centralized location. When the audio source is provided locally, the multi-zone audio system functions as a collection of many stereo systems, making source sharing difficult. When the audio source is provided centrally, the centralized location may include a juke box, many compact discs, an AM or FM radio, tapes, or others. To send an audio source to an audio player demanding such source, a cross-bar type of device is used to prevent the audio source from going to other audio players that may be playing other audio sources.

**[0005]** In order to achieve playing different audio sources in different audio players, the traditional multi-zone audio system is generally either hard-wired or controlled by a pre-configured and pre-programmed controller. While the pre-programmed configuration may be satisfactory in one situation, it may not be suitable for another situation. For example, a person would like to listen to broadcast news from his/her favorite radio station in a bedroom, a bathroom and a den while preparing to go to work in the morning. The same person may wish to listen in the den and the living room to music from a compact disc in the evening. In order to satisfy such requirements, two groups of audio players must be established. In the morning, the audio players in the bedroom, the bathroom and the den need to be grouped for the broadcast news. In the evening, the audio players in the den and the living room are grouped for the music. Over the weekend, the audio players in the den, the living room, and a kitchen are grouped for party music. Because the morning group, the evening group and the weekend group contain the den, it can be difficult for the traditional

system to accommodate the requirement of dynamically managing the ad hoc creation and deletion of groups.

**[0006]** There is a need for dynamic control of the audio players as a group. With a minimum manipulation, the audio players may be readily grouped. In a traditional multi-zone audio system, the audio players have to be adjusted one at a time, resulting in an inconvenient and non-homogenous audio environment. Further, there is a need to individually or systematically adjust the audio volume of the audio players.

## **SUMMARY OF THE INVENTION**

**[0007]** This section is for the purpose of summarizing some aspects of the present invention and to briefly introduce some preferred embodiments. Simplifications or omissions in this section as well as in the abstract or the title of this description may be made to avoid obscuring the purpose of this section, the abstract and the title. Such simplifications or omissions are not intended to limit the scope of the present invention.

**[0008]** In general, the present invention pertains to controlling a plurality of multimedia players, or simply players, in groups. According to one aspect of the present invention, a mechanism is provided to allow a user to group some of the players according to a theme or scene, where each of the players is located in a zone. When the scene is activated, the players in the scene react in a synchronized manner. For example, the players in the scene are all caused to play an audio source or music in a playlist, wherein the audio source may be located anywhere on a network.

**[0009]** According to another aspect of the present invention, the scene may be activated at any time or a specific time. A user may activate the scene at any time so that only some selected zones in an entertainment system facilitate a playback of an

audio source. When the scene is activated at a specific time, the scene may be used as an alarm or buzzer.

**[0010]** According to still another aspect of the present invention, a controlling device (also referred to herein as controller) is provided to facilitate a user to select any of the players in the system to form respective groups each of which is set up per a scene. Although various scenes may be saved in any of the members in a group, commands are preferably sent from the controller to the rest of the members when one of the scenes is executed. Depending on implementation, the commands include parameters pertaining to identifiers of the players, volumes settings, audio source and etc.

**[0011]** According to yet another aspect of the present invention, a configurable module is implemented in the controlling device that provides interactive graphic user interface for forming, managing and controlling groups in the system, de-grouping a group or adjusting audio volume of individual players or a group of players.

**[0012]** The present invention may be implemented in many forms including software, hardware or a combination of both. According to one embodiment, the present invention is directed to a method for groupings in a multi-zone media system, the method comprises providing a mechanism to allow a user to determine which players in the system to be associated with a theme representing a group; and configuring the theme with parameters pertaining to the players, wherein the theme is activated at anytime or a specific time so that the players react in a synchronized manner. The players in a scene are synchronized to play a multimedia file when the scene is activated.

**[0013]** According to another embodiment, the present invention is directed to an entertainment system for grouping players, the system comprises: a plurality of players,



each located in one zone; and a controller providing a mechanism to allow a user to select which of the players to be associated with a theme representing a group; and configure the theme with parameters pertaining to the selected players, wherein the theme is activated at anytime or a specific time so that the selected players react in a synchronized manner. As a result, the selected players are synchronized to play a multimedia that is in a digital format and retrieved from a source over a network.

**[0014]** One of the objects, features, and advantages of the present invention is to remotely control a plurality of multimedia players in a multi-zone system, playing and controlling the audio source synchronously if the players are grouped together, or playing and controlling the audio source individually if the players are disassociated with each other.

**[0015]** Other objects, features, and advantages of the present invention will become apparent upon examining the following detailed description of an embodiment thereof, taken in conjunction with the attached drawings.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

**[0016]** These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims, and accompanying drawings where:

**[0017]** FIG. 1 shows an exemplary configuration in which the present invention may be practiced;

**[0018]** FIG. 2A shows an exemplary functional block diagram of a player in accordance with the present invention;

**[0019]** FIG. 2B shows an example of a controller that may be used to remotely control one of more players of FIG. 2A;

**[0020]** FIG. 2C shows an exemplary internal functional block diagram of a controller in accordance with one embodiment of the present invention;

**[0021]** FIG. 3A provides an illustration of one zone scene, where the left column shows the starting zone grouping – all zones are separate, the column on the right shows the effects of grouping the zones to make a group of 3 zones named after “Morning”;

**[0022]** FIG. 3B shows that a user defines multiple groups to be gathered at the same time;

**[0023]** FIG. 4 shows an exemplary user interface that may be displayed on a controller or a computer of FIG. 1;

**[0024]** FIG. 5A shows a user interface to allow a user to form a scene;

**[0025]** FIG. 5B shows another user interface **520** to allow a user to form a scene;

**[0026]** FIG. 5C shows a user interface to allow a user to adjust a volume level of the zone players in a zone scene individually or collectively; and

**[0027]** FIG. 6 shows a flowchart or process of providing a player theme or a zone scene for a plurality of players, where one or more of the players are placed in a zone.

## **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

**[0028]** The detailed description of the invention is presented largely in terms of procedures in terms of procedures, steps, logic blocks, processing, and other symbolic

representations that directly or indirectly resemble the operations of data processing devices coupled to networks. These process descriptions and representations are typically used by those skilled in the art to most effectively convey the substance of their work to others skilled in the art. Numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will become obvious to those skilled in the art that the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the present invention.

**[0029]** Reference herein to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the invention. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Further, the order of blocks in process flowcharts or diagrams representing one or more embodiments of the invention do not inherently indicate any particular order nor imply any limitations in the invention.

**[0030]** Referring now to the drawings, in which like numerals refer to like parts throughout the several views. FIG. 1 shows an exemplary configuration **100** in which the present invention may be practiced. The configuration may represent, but not be limited to, a part of a residential home, a business building or a complex with multiple zones. There are a number of multimedia players of which three examples **102**, **104** and **106** are shown as audio devices. Each of the audio devices may be installed or provided in one particular area or zone and hence referred to as a zone player herein.

**[0031]** As used herein, unless explicitly stated otherwise, an audio source or audio sources are in digital format and can be transported or streamed over a data network. To facilitate the understanding of the present invention, it is assumed that the configuration **100** represents a home. Thus, the zone player **102** and **104** may be located in two of the bedrooms respectively while the zone player **106** may be installed in a living room. All of the zone players **102**, **104** and **106** are coupled directly or indirectly to a data network **108**. In addition, a computing device **110** is shown to be coupled on the network **108**. In reality, any other devices such as a home gateway device, a storage device, or an MP3 player may be coupled to the network **108** as well.

**[0032]** The network **108** may be a wired network, a wireless network or a combination of both. In one example, all devices including the zone players **102**, **104** and **106** are coupled to the network **108** by wireless means based on an industry standard such as IEEE 802.11. In yet another example, all devices including the zone players **102**, **104** and **106** are part of a local area network that communicates with a wide area network (e.g., the Internet).

**[0033]** Many devices on the network **108** are configured to download and store audio sources. For example, the computing device **110** can download audio sources from the Internet and store the downloaded sources locally for sharing with other devices on the Internet or the network **108**. The computing device **110** or any of the zone players can also be configured to receive streaming audio. Shown as a stereo system, the device **112** is configured to receive an analog audio source (e.g., from broadcasting) or retrieve a digital audio source (e.g., from a compact disk). The analog audio sources can be converted to digital audio sources. In accordance with the present invention, the audio source may be shared among the devices on the network **108**.



**[0034]** Two or more zone players may be grouped together to form a new zone group. Any combinations of zone players and an existing zone group may be grouped together. In one instance, a new zone group is formed by adding one zone player to another zone player or an existing zone group.

**[0035]** Referring now to FIG. 2A, there is shown an exemplary functional block diagram of a zone player **200** in accordance with the present invention. The zone player **200** includes a network interface **202**, a processor **204**, a memory **206**, an audio processing circuit **210**, a module **212**, and optionally, an audio amplifier **214** that may be internal or external. The network interface **202** facilitates a data flow between a data network (i.e., the data network **108** of FIG. 1) and the zone player **200** and typically executes a special set of rules (i.e., a protocol) to send data back and forth. One of the common protocols used in the Internet is TCP/IP (Transmission Control Protocol/Internet Protocol). In general, a network interface manages the assembling of an audio source or file into smaller packets that are transmitted over the data network or reassembles received packets into the original source or file. In addition, the network interface **202** handles the address part of each packet so that it gets to the right destination or intercepts packets destined for the zone player **200**.

**[0036]** The network interface **202** may include one or both of a wireless interface **216** and a wired interface **217**. The wireless interface **216**, also referred to as a RF interface, provides network interface functions by a wireless means for the zone player **200** to communicate with other devices in accordance with a communication protocol (such as the wireless standard IEEE 802.11a, 802.11b or 802.11g). The wired interface **217** provides network interface functions by a wired means (e.g., an Ethernet cable). In one embodiment, a zone player includes both of the interfaces **216** and **217**, and other zone players include only a RF or wired interface. Thus these other zone players communicate with other devices on a network or retrieve audio sources via the zone

player. The processor **204** is configured to control the operation of other parts in the zone player **200**. The memory **206** may be loaded with one or more software modules that can be executed by the processor **204** to achieve desired tasks. According to one aspect of the present invention, a software module implementing one embodiment of the present invention is executed, the processor **204** operates in accordance with the software module in reference to a saved zone group configuration characterizing a zone group created by a user, the zone player **200** is caused to retrieve an audio source from another zone player or a device on the network.

**[0037]** According to one embodiment of the present invention, the memory **206** is used to save one or more saved zone configuration files that may be retrieved for modification at any time. Typically, a saved zone group configuration file is transmitted to a controller (e.g., the controlling device **140** or **142** of FIG. 1, a computer, a portable device, or a TV) when a user operates the controlling device. The zone group configuration provides an interactive user interface so that various manipulations or control of the zone players may be performed.

**[0038]** The audio processing circuit **210** resembles most of the circuitry in an audio playback device and includes one or more digital-to-analog converters (DAC), an audio preprocessing part, an audio enhancement part or a digital signal processor and others. In operation, when an audio source is retrieved via the network interface **202**, the audio source is processed in the audio processing circuit **210** to produce analog audio signals. The processed analog audio signals are then provided to the audio amplifier **214** for playback on speakers. In addition, the audio processing circuit **210** may include necessary circuitry to process analog signals as inputs to produce digital signals for sharing with other devices on a network.

**[0039]** Depending on an exact implementation, the module **212** may be implemented as a combination of hardware and software. In one embodiment, the module **212** is used to save a scene. The audio amplifier **214** is typically an analog circuit that powers the provided analog audio signals to drive one or more speakers.

**[0040]** Referring now to FIG. 2B, there is shown an exemplary controller **240**, which may correspond to the controlling device **140** or **142** of FIG. 1. The controller **240** may be used to facilitate the control of multi-media applications, automation and others in a complex. In particular, the controller **240** is configured to facilitate a selection of a plurality of audio sources available on the network, controlling operations of one or more zone players (e.g., the zone player **200**) through a RF interface corresponding to the RF interface **216** of FIG. 2A. According to one embodiment, the wireless means is based on an industry standard (e.g., infrared, radio, wireless standard IEEE 802.11a, 802.11b or 802.11g). When a particular audio source is being played in the zone player **200**, a picture, if there is any, associated with the audio source may be transmitted from the zone player **200** to the controller **240** for display. In one embodiment, the controller **240** is used to synchronize more than one zone players by grouping the zone players in a group. In another embodiment, the controller **240** is used to control the volume of each of the zone players in a zone group individually or together.

**[0041]** The user interface for the controller **240** includes a screen **242** (e.g., a LCD screen) and a set of functional buttons as follows: a “zones” button **244**, a “back” button **246**, a “music” button **248**, a scroll wheel **250**, “ok” button **252**, a set of transport control buttons **254**, a mute button **262**, a volume up/down button **264**, a set of soft buttons **266** corresponding to the labels **268** displayed on the screen **242**.

**[0042]** The screen **242** displays various screen menus in response to a user’s selection. In one embodiment, the “zones” button **244** activates a zone management



screen or “Zone Menu”, which is described in more details below. The “back” button **246** may lead to different actions depending on the current screen. In one embodiment, the “back” button triggers the current screen display to go back to a previous one. In another embodiment, the “back” button negates the user’s erroneous selection. The “music” button **248** activates a music menu, which allows the selection of an audio source (e.g., a song) to be added to a zone player’s music queue for playback.

**[0043]** The scroll wheel **250** is used for selecting an item within a list, whenever a list is presented on the screen **242**. When the items in the list are too many to be accommodated in one screen display, a scroll indicator such as a scroll bar or a scroll arrow is displayed beside the list. When the scroll indicator is displayed, a user may rotate the scroll wheel **250** to either choose a displayed item or display a hidden item in the list. The “ok” button **252** is used to confirm the user selection on the screen **242**.

**[0044]** There are three transport buttons **254**, which are used to control the effect of the currently playing song. For example, the functions of the transport buttons may include play/pause and forward/rewind a song, move forward to a next song track, or move backward to a previous track. According to one embodiment, pressing one of the volume control buttons such as the mute button **262** or the volume up/down button **264** activates a volume panel. In addition, there are three soft buttons **266** that can be activated in accordance with the labels **268** on the screen **242**. It can be understood that, in a multi-zone system, there may be multiple audio sources being played respectively in more than one zone players. The music transport functions described herein shall apply selectively to one of the sources when a corresponding one of the zone players or zone groups is selected.

**[0045]** FIG. 2C illustrates an internal functional block diagram of an exemplary controller **270**, which may correspond to the controller **240** of FIG. 2B. The screen **272**



on the controller **270** may be a LCD screen. The screen **272** communicates with and is commanded by a screen driver **274** that is controlled by a microcontroller (e.g., a processor) **276**. The memory **282** may be loaded with one or more application modules **284** that can be executed by the microcontroller **276** with or without a user input via the user interface **278** to achieve desired tasks. In one embodiment, an application module is configured to facilitate grouping a number of selected zone players into a zone group and synchronizing the zone players for one audio source. In another embodiment, an application module is configured to control together the audio volumes of the zone players in a zone group. In operation, when the microcontroller **276** executes one of the application modules **284**, the screen driver **274** generates control signals to drive the screen **272** to display an application specific user interface accordingly, more of which will be described below.

**[0046]** The controller **270** includes a network interface **280** referred to as a RF interface **280** that facilitates wireless communication with a zone player via a corresponding RF interface thereof. In one embodiment, the commands such as volume control and audio playback synchronization are sent via the RF interfaces. In another embodiment, a saved zone group configuration is transmitted between a zone player and a controller via the RF interfaces. The controller **270** may control one or more zone players, such as **102**, **104** and **106** of FIG. 1. Nevertheless, there may be more than one controllers, each preferably in a zone (e.g., a room) and configured to control any one and all of the zone players.

**[0047]** In one embodiment, a user creates a zone group including at least two zone players from the controller **240** that sends signals or data to one of the zone players. As all the zone players are coupled on a network, the received signals in one zone player can cause other zone players in the group to be synchronized so that all the zone players in the group playback an identical audio source or a list of identical audio

sources in a timely synchronized manner. Similarly, when a user increases the audio volume of the group from the controller, the signals or data of increasing the audio volume for the group are sent to one of the zone players and causes other zone players in the group to be increased together in volume and in scale.

**[0048]** According to one implementation, an application module is loaded in memory **282** for zone group management. When a predetermined key (e.g. the “zones” button **244**) is activated on the controller **240**, the application module is executed in the microcontroller **276**. The input interface **278** coupled to and controlled by the microcontroller **276** receives inputs from a user. A “Zone Menu” is then displayed on the screen **272**. The user may start grouping zone players into a zone group by activating a “Link Zones” or “Add Zone” soft button, or de-grouping a zone group by activating an “Unlink Zones” or “Drop Zone” button. The detail of the zone group manipulation will be further discussed below.

**[0049]** As described above, the input interface **278** includes a number of function buttons as well as a screen graphical user interface. It should be pointed out that the controller **240** in FIG. 2B is not the only controlling device that may practice the present invention. Other devices that provide the equivalent control functions (e.g., a computing device, a hand-held device) may also be configured to practice the present invention. In the above description, unless otherwise specifically described, it is clear that keys or buttons are generally referred to as either the physical buttons or soft buttons, enabling a user to enter a command or data.

**[0050]** One mechanism for ‘joining’ zone players together for music playback is to link a number of zone players together to form a group. To link a number of zone players together, a user may manually link each zone player or room one after the other. For example, there is a multi-zone system that includes the following zones.

Bathroom

Bedroom

Den

Dining Room

Family Room

Foyer

**[0051]** If the user wishes to link 5 of the 6 zone players using the current mechanism, he/she must start with a single zone and then manually link each zone to that zone. This mechanism may be sometimes quite time consuming. According to one embodiment, a set of zones can be dynamically linked together using one command. Using what is referred to herein as a theme or a zone scene, zones can be configured in a particular scene (e.g., morning, afternoon, or garden), where a predefined zone grouping and setting of attributes for the grouping are automatically effectuated.

**[0052]** For instance, a “Morning” zone scene/configuration command would link the Bedroom, Den and Dining Room together in one action. Without this single command, the user would need to manually and individually link each zone. FIG. 3A provides an illustration of one zone scene, where the left column shows the starting zone grouping – all zones are separate, the column on the right shows the effects of grouping the zones to make a group of 3 zones named after “Morning”.

**[0053]** Expanding this idea further, a Zone Scene can be set to create multiple sets of linked zones. For example, a scene creates 3 separate groups of zones, the downstairs zones would be linked together, the upstairs zones would be linked together in their own group, and the outside zones (in this case the patio) would move into a group of its own.

**[0054]** In one embodiment as shown in FIG. 3B, a user defines multiple groups to be gathered at the same time. For example: an “Evening Scene” is desired to link the following zones:

- Group1
  - Bedroom
  - Den
  - Dining Room
- Group 2
  - Garage
  - Garden

where Bathroom, Family Room and Foyer should be separated from any group if they were part of a group before the Zone Scene was invoked.

**[0055]** One important of the features, benefits and objects in the present invention is that that zones do not need to be separated before a zone scene is invoked. In one embodiment, a command is provided and links all zones in one step, if invoked. The command is in a form of a zone scene. After linking the appropriate zones, a zone scene command could apply the following attributes:

Set volumes levels in each zones (each zone can have a different volume)

Mute/Unmute zones.

Select and play specific music in the zones.

Set the play mode of the music (Shuffle, Repeat, Shuffle-repeat)

Set the music playback equalization of each zone (e.g., bass treble).

**[0056]** A further extension of this embodiment is to trigger a zone scene command as an alarm clock function. For instance the zone scene is set to apply at 8:00am. It could link appropriate zones automatically, set specific music to play and



then stop the music after a defined duration. Although a single zone may be assigned to an alarm, a scene set as an alarm clock provides a synchronized alarm, allowing any zones linked in the scene to play a predefined audio (e.g., a favorable song, a predefined playlist) at a specific time or for a specific duration. If, for any reason, the scheduled music failed to be played (e.g., an empty playlist, no connection to a share, failed UPnP, no Internet connection for an Internet Radio station), a backup buzzer will sound. This buzzer will be a sound file that is stored in a zone player.

**[0057]** FIG. 4 shows an exemplary user interface **400** that may be displayed on a controller **142** or a computer **110** of FIG. 1. The interface **400** shows a list of items that may be set up by a user to cause a scene to function at a specific time. In the embodiment shown in FIG. 4, the list of items includes “Alarm”, “Time”, “Zone”, “Music”, “Frequency” and “Alarm length”. “Alarm” can be set on or off. When “Alarm” is set on, “Time” is a specific time to set off the alarm. “Zone” shows which zone players are being set to play a specified audio at the specific time. “Music” shows what to be played when the specific time arrives. “Frequency” allows the user to define a frequency of the alarm. “Alarm length” defines how long the audio is to be played. It should be noted that the user interface **400** is provided herein to show some of the functions associated with setting up an alarm. Depending on an exact implementation, other functions, such as time zone, daylight savings, time synchronization, and time/date format for display may also be provided without departing from the present invention.

**[0058]** According to one embodiment, each zone player in a scene may be set up for different alarms. For example, a “Morning” scene includes three zone players, each in a bedroom, a den, and a dining room. After selecting the scene, the user may set up an alarm for the scene as whole. As a result, each of the zone players will be activated at a specific time.

**[0059]** FIG. 5A shows a user interface **500** to allow a user to form a scene. The panel on the left shows the available zones in a household. The panel on the right shows the zones that have been selected and be grouped as part of this scene. Depending on an exact implementation of a user interface, Add/Remove buttons may be provided to move zones between the panels, or zones may be dragged along between panels.

**[0060]** FIG. 5B shows another user interface **520** to allow a user to form a scene. The user interface **520** that may be displayed on a controller or a computing device, lists available zones in a system. A checkbox is provide next to each of the zones so that a user may check in the zones to be associated with the scene.

**[0061]** FIG. 5C shows a user interface **510** to allow a user to adjust a volume level of the zone players in a zone scene individually or collectively. As shown in the user interface **510**, the 'Volumes...' button (shown as sliders, other forms are possible) allows the user to affect the volumes of the associated zone players when a zone scene is invoked. In one embodiment, the zone players can be set to retain whatever volume that they currently have when the scene is invoked. Additionally the user can decide if the volumes should be unmuted or muted when the scene is invoked.

**[0062]** FIG. 6 shows a flowchart or process **600** of providing a player theme or a zone scene for a plurality of players, where one or more of the players are placed in a zone. The process **600** is presented in accordance with one embodiment of the present invention and may be implemented in a module to be located in the memory **282** of FIG. 2C.

**[0063]** The process **600** is initiated only when a user decides to proceed with a zone scene at **602**. The process **600** then moves to **604** where it allows a user to decide which zone players to be associated with the scene. For example, there are ten players

in a household, and the scene is named after “Morning”. The user may be given an interface to select four of the ten players to be associated with the scene. At **606**, the scene is saved. The scene may be saved in any one of the members in the scene. In the example of FIG. 1, the scene is saved in one of the zone players and displayed on the controller **142**. In operation, a set of data pertaining to the scene includes a plurality of parameters. In one embodiment, the parameters include, but may not be limited to, identifiers (e.g., IP address) of the associated players and a playlist. The parameters may also include volume/tone settings for the associated players in the scene. The user may go back to **602** to configure another scene if desired.

**[0064]** Given a saved scene, a user may activate the scene at any time or set up a timer to activate the scene at **610**. The process **600** can continue when a saved scene is activated at **610**. At **612**, upon the activation of a saved scene, the process **600** checks the status of the players associated with the scene. The status of the players means that each of the players shall be in condition to react in a synchronized manner. In one embodiment, the interconnections of the players are checked to make sure that the players communicate among themselves and/or with a controller if there is such a controller in the scene.

**[0065]** It is assumed that all players associated with the scene are in good condition. At **614**, commands are executed with the parameters (e.g., pertaining to a playlist and volumes). In one embodiment, data including the parameters is transported from a member (e.g., a controller) to other members in the scene so that the players are caused to synchronize an operation configured in the scene. The operation may cause all players to play back a song in identical or different volumes or to play back a pre-stored file.

**[0066]** One of the features, benefits and advantages in the present invention is to allow sets of related devices (controllers and operating components) to exist as a group without interfering with other components that are potentially visible on the same wired or wireless network. Each of the sets is configured to a theme or a scene.

**[0067]** The present invention has been described in sufficient detail with a certain degree of particularity. It is understood to those skilled in the art that the present disclosure of embodiments has been made by way of examples only and that numerous changes in the arrangement and combination of parts may be resorted without departing from the spirit and scope of the invention as claimed. While the embodiments discussed herein may appear to include some limitations as to the presentation of the information units, in terms of the format and arrangement, the invention has applicability well beyond such embodiment, which can be appreciated by those skilled in the art. Accordingly, the scope of the present invention is defined by the appended claims rather than the forgoing description of embodiments.



## Claims

1. In a network comprising a plurality of zone players, a method comprising:  
receiving via the network by a controller device, a zone configuration from one of the plurality of zone players, wherein the zone configuration is maintained at one or more of the plurality of zone players, and wherein the zone configuration characterizes one or more zone scenes created by a user, each zone scene comprising at least one zone group, each zone group including at least one of the plurality of zone players, and each zone player in the zone group configured to synchronously playback multimedia content from a multimedia source with another zone player in the zone group;  
receiving, by the controller device, a user input to modify the zone configuration;  
based on the user input, modifying, by the controller device, the zone configuration; and  
transmitting, by the controller device to one of the plurality of zone players, the modified zone configuration to facilitate synchronized playback of multimedia content in accordance with the modified zone configuration, wherein the modified zone configuration identifies a first multimedia source for playback by a first zone group associated with a first zone scene and a second multimedia source for playback by a second zone group associated with the first zone scene.
2. The method of claim 1, wherein the modified zone configuration is maintained by the one of the plurality of zone players.
3. The method of claim 1, wherein the modified zone configuration further comprises one or more attributes associated with the one or more zone scenes.

4. The method of claim 3, wherein the one or more attributes comprises one or more of (i) a volume level for audio playback for each zone player in the one or more zone scenes, (ii) a mute or unmute setting for audio playback, (iii) a selection and play of specific music, (iv) a play mode setting, (v) an equalization setting for audio playback, and (vi) an audio alarm.

5. The method of claim 1, wherein the modified zone configuration further comprises a name associated with each of the one or more zone scenes.

6. The method of claim 1, wherein multimedia content comprises a first multimedia content from a first multimedia source and a second multimedia content from a second multimedia source.

7. The method of claim 6, wherein the first multimedia content comprises an internet radio stream.

8. The method of claim 1, wherein the user input to modify the zone configuration comprises an input selecting a specified zone scene from a list of one or more zone scenes.

9. A multimedia controller including a processor, the controller configured to:  
receive, via a network interface, a zone configuration from one of the plurality of zone players, wherein the zone configuration is maintained at one or more of the plurality of zone players, and wherein the zone configuration characterizes one or more zone scenes created by a

user, each zone scene comprising at least one zone group each zone group including at least one of the plurality of zone players, and each zone player in the zone group configured to synchronously playback multimedia content from a multimedia source with another zone player in the zone group;

receive a user input to modify the zone configuration;

based on the user input, modify, the zone configuration; and

transmit to one of the plurality of zone players, the modified zone configuration to facilitate synchronized playback of multimedia content in accordance with the modified zone configuration, wherein the modified zone configuration identifies a first multimedia source for playback by a first zone group associated with a first zone scene and a second multimedia source for playback by a second zone group associated with the first zone scene.

10. The multimedia controller of claim 9, wherein the modified zone configuration is maintained by the one of the plurality of zone players.

11. The multimedia controller of claim 9, wherein the modified zone configuration further comprises one or more attributes associated with the one or more zone scenes.

12. The multimedia controller of claim 11, wherein the one or more attributes comprises one or more of (i) a volume level for audio playback for each zone player in the one or more zone scenes, (ii) a mute or unmute setting for audio playback, (iii) a selection and play of specific music, (iv) a play mode setting, (v) an equalization setting for audio playback, and (vi) an audio alarm.

13. The multimedia controller of claim 9, wherein the modified zone configuration further comprises a name associated with each of the one or more zone scenes.

14. The multimedia controller of claim 9, wherein multimedia content comprises a first multimedia content from a first multimedia source and a second multimedia content from a second multimedia source.

15. The multimedia controller of claim 14, wherein the first multimedia content comprises an internet radio stream.

16. The multimedia controller of claim 9, wherein the user input to modify the zone configuration comprises an input selecting a specified zone scene from a list of zone scenes.

17. A non-transitory computer-readable storage medium including a set of instructions for execution by a processor, the set of instructions, when executed, implement a controller configured to:

receive, via a network interface, a zone configuration from one of the plurality of zone players, wherein the zone configuration is maintained at one or more of the plurality of zone players, and wherein the zone configuration characterizes one or more zone scenes created by a user, each zone scene comprising at least one zone group each zone group including at least one of the plurality of zone players, and each zone player in the zone group configured to

synchronously playback multimedia content from a multimedia source with another zone player in the zone group;

receive a user input to modify the zone configuration;

based on the user input, modify, the zone configuration; and

transmit to one of the plurality of zone players, the modified zone configuration to facilitate synchronized playback of multimedia content in accordance with the modified zone configuration, wherein the modified zone configuration identifies a first multimedia source for playback by a first zone group associated with a first zone scene and a second multimedia source for playback by a second zone group associated with the first zone scene.

18. The computer-readable medium of claim 17, wherein the modified zone configuration is maintained by the one of the plurality of zone players.


19. The computer-readable medium of claim 17, wherein the modified zone configuration further comprises one or more attributes associated with the one or more zone scenes.

20. The computer-readable medium of claim 19, wherein the one or more attributes comprises one or more of (i) a volume level for audio playback for each zone player in the one or more zone scenes, (ii) a mute or unmute setting for audio playback, (iii) a selection and play of specific music, (iv) a play mode setting, (v) an equalization setting for audio playback, and (vi) an audio alarm.


## **Controlling and manipulating groupings in a multi-zone media system**

### **Abstract**


In general, techniques of controlling a plurality of multimedia players in groups are disclosed. According to one aspect of the present invention, a mechanism is provided to allow a user to group some of the players according to a theme or scene, where each of the players is located in a zone. When the scene is activated, the players in the scene react in a synchronized manner. For example, the players in the scene are all caused to play a multimedia source or music in a playlist, wherein the multimedia source may be located anywhere on a network.




**FIG. 2A**












**FIG. 2C**



**FIG. 3A**




**FIG. 3B**




**FIG. 4**







**FIG. 5A**



**FIG. 5B**



**FIG. 5C**



**FIG. 6**